XI PLEATED + CELLULAR SHADES MEASURE INSTRUCTIONS

ORDER IN 4 EASY STEPS

I. Select Mount Type:

Inside:

- Mounted within the window frame
- Provides a clean, built-in look
- Great way to leave attractive woodwork exposed
- •If window frame isn't deep enough, please select outside mount



Outside:


- Great option when there is not enough depth for an inside mount
- •Mounted to the wall, ceiling or molding surface surrounding the window
- Often used to make the window appear larger or to hide a less attractive window or door
- •No minimum depth requirement



2. Measure:

Inside:


STEP 1: Measure the inside width at 3 locations – the top, middle and bottom. Record the smallest of the 3 measurements. This is your ordering width. We will make the necessary deductions (approx. $\frac{1}{4}$ " – $\frac{3}{8}$ ")





Outside:

STEP 1: Measure the width of the area you wish to cover. If space allows we recommend adding 2-3" ($1-1\frac{1}{2}$ " each side) to this measurement to help eliminate light seepage. This is your ordering width and will be the overall measurement of the shade.





3. Select Control Type:

Standard Cord Lock:

- •Allows you to raise and lower shade and lock in place
- As shade is raised, cord length increases
- •Cleat included to wrap cord around for clean look and child safety
- •No charge

Continuous Loop Control:

- Continuous cord allows for easy operation
- •The cord always remains the same length no matter what position the shade is in
- Makes operating larger shades easier
- Surcharge applies

Cordless:

- •Eliminate exposed cords
- Easy to adjust by lifting or lowering the shade with a gentle push or pull on the bottom rail
- Eliminates danger of dangling cords to children and pets
- •Surcharge applies

4. Select Control Position: Left or Right

- This is the side of the shade that your control will hang from (left or right)
- Consider any obstacles that may interfere with operation (door handle, window opener, furniture location, etc.)

Mounting Requirements:

Product	Minimum Depth to Install	Minimum Depth for Flush Mount	Minimum Space for Outside Mount
with cord lock	5/8"	23/8"	5/8″
with continuous loop	7/8"	21/4"	13/4"
with top down bottom up	5/8"	23/8"	5/8″
with cordless system	7/8"	21/4"	1¾"

+ Optional Features:

Top Down / Bottom Up:

- Dual operation allows you to control privacy while still allowing light in
- •Shade can be lowered from the top down and raised from the bottom up
- •Not available with continuous loop control
- ·Surcharge applies



2 Shades on I Headrail:

- •2 shades hang from the same headrail and operate independently
- Total width you provide will be divided equally making both shades equal size (contact us for special requests)
- •Small gap (approximately $\frac{1}{2}$ ") will exist between the 2 shades
- Surcharge applies
- •Controls will be positioned on the outside of each shade
- •Available with standard cord lock only
- Not available for XL Pleated Shades

